

D

D

C


C

B

B

A


A

**Notes:**

1. F CLK signal is an external input clock signal.  
It is recommended that F CLK signal be provided through an active oscillator crystal.
2. It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
B	GW1N-LV2QN88	2.0

Date: Wednesday, April 26, 2023 Sheet 1 of 5

**Notes:**








1. F\_CLK signal is an external input clock signal.

It is recommended that F\_CLK signal be provided through an active oscillator crystal.

2. It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		Gowin FPGA-AUTOMOTIVE Minimum System Diagram	
Size	Document Number	Rev	2.0
B	GW1N-LV4QN88	Date:	Wednesday, April 26, 2023
		Sheet	2 of 5


# GW1NZ-LV1QN48



## Notes:

1. F\_CLK signal is an external input clock signal.  
It is recommended that F\_CLK signal be provided through an active oscillator crystal.
2. It is recommended that add an ESD protection chip to the JTAG download circuit.

Title		
Gowin FPGA-AUTOMOTIVE Minimum System Diagram		
Size	Document Number	Rev
A4	GW1NZ-LV1QN48	2.0
Date:	Wednesday, April 26, 2023	Sheet 3 of 5



## Notes:

1. F\_CLK signal is an external input clock signal.







It is recommended that F\_CLK signal be provided through an active oscillator crystal.

2. External Flash memory is used to store downloaded programs.

For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.

3. It is recommended that add an ESD protection chip to the JTAG download circuit.

Title	Gowin FPGA-AUTOMOTIVE Minimum System Diagram	
Size	Document Number	Rev
A3	GW2A-LV18PG256	2.0
Date	Wednesday, April 26, 2023	Sheet 4 of 5

**Notes:**

1. F\_CLK signal is an external input clock signal.  
It is recommended that F\_CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs.  
For details about SPI Flash model selection, see Chapter 10 SPI Flash Selection in UG290.
3. It is recommended that add an ESD protection chip to the JTAG download circuit.